

**FIBER OPTIC DISTRIBUTION BOX  
SPECIFICATION**<sup>®</sup>

**TUOLIMA**

**GFX-04B**





## Specification

ITEM	Weight	Dimension (L×W×H mm)	In/out port	Max. port size(mm)	Max. capacity	PLC Splitter
GFX-04B	0.58KG	225×195×50	3cable inlets+8mini drop cable outlets+1bigger drop cable outlet	Φ13 for 2inlets, Φ5 for 8outlets, Φ11 for 1outlet	8F	1*8 mini PLC

## Description

The equipment is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile it provides solid protection and management for the FTTx network building.

## Features

- 1) Wet-proof water-proof dust-proof anti-aging, protection level up to IP65
- 2) Clamping for feeder cable and drop cable, fiber splitting, splicing, fixation, storage, distribution...etc all in one
- 3) Up to 1\*8 Mini PLC Splitter
- 4) 3 pcs uncut cable inlets

## ORDERING INFORMATION

- ① Empty Box without Adapters
- ② Box full with 8pcs SC APC SM SX Adapter
- ③ Box full with 8pcs SC UPC SM SX Adapter
- ④ Box full with 8pcs SC APC SM SX Adapter+8pcs Pigtails
- ⑤ Box full with 8pcs SC UPC SM SX Adapter+8pcs Pigtails
- ⑥ Box with 8pcs adapters&1pcs 1:8 mini PLC Splitter
- ⑦ Box with 1pcs card PLC Splitter

## Application

- 1) Widely used in FTTH access network.
- 2) Telecommunication Networks
- 3) CATV Networks
- 4) Data communications Networks
- 5) Local Area Networks