

**FIBER OPTIC FACEPLATE BOX
SPECIFICATION**

GFX-06A



TUOLIMA

SPECIFICATION

| MODEL | Dimension (L×Wmm) | Adapter Type | Max. Capacity | Color | Material |
|---------|----------------------|------------------|---------------|----------------------------|----------|
| GFX-06A | 225*200*65mm | SC APC SC UPC | 12FO | White/Black/ Light Gray | ABS |

ORDERING INFORMATION

- ① Empty Box without Adapters
- ② Box full with 16pcs SC APC SM SX Adapter
- ③ Box full with 16pcs SC UPC SM SX Adapter
- ④ Box full with 16pcs SC Adapter+1pcs Mini Splitter
- ⑤ Box full with 1PCS 1*16 Insert Splitter

DESCRIPTION

The equipment is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile it provides solid protection and management for the FTTx network building.

FEATURES

- 1) With protective doors, Dust Proof.
- 2) Suitable for many types of modules, used in cabling work area subsystem.
- 3) Embedded type surface, easy for installation and removal.
- 4) Available for fiber optical SC simplex or LC duplex and can be used in both surface mounted installation and concealed panel installation
- 5) All modules are solderless mode.

Application

- 1). Optical fiber communication system.
- 2). Fiber optical CATV, FTTH Fiber to the home.
- 3). Optical fiber access network.
- 4). Testing instruments, fiber optical sensors.
- 5). Fiber optical patch panel, cabinet type or wall-mounted type fiber optical distribution system.