

BU600E

BU Series


Fire-resistant UPS with The Most Durable Capability For Protection



Featuring the best-in-class plastic housing, the BU UPS Series provides an outstanding fire-resistant capability to minimize the possible damages of valuable assets in case of any fire incident.

With CyberPower's innovative Battery Management Technology, the UPS significantly optimizes the charging process and battery performance. The configurable alarm allows users to switch ON/OFF the audible alarm when UPS is on battery mode to avoid any disturbance. Its generator compatibility provides an extensive application scenario during a power outage.

With the built-in Automatic Voltage Regulation (AVR) stabilizing the AC signal and maintaining a safe voltage, the UPS maintains safe power levels through Boost and Buck function for the connected equipment without resorting to battery power.



APPLICATIONS

- Home and Home Office
- Small Office

SERIES FEATURES

- Automatic Voltage Regulation (AVR)
- Generator Compatible
- Overload Protection
- EMI, RFI, Surge and Spike Protection
- LED Status Indicator
- Fire-resistant Capability
- Configurable Alarm
- Battery Management Technology
- Compact Size

AUTOMATIC VOLTAGE REGULATION



Automatic Voltage Regulation provides clean, consistent AC power by automatically regulating low voltages and over voltages within defined tolerances, when incoming utility power has minor fluctuations.



FIRE-RESISTANT CAPABILITY

CyberPower adopts the best-in-class plastics in the industry. The outstanding fire resistant capability minimizes the possible damage of your valuable assets in case of any fire incident.

TECHNICAL SPECIFICATIONS

Model Name	BU600E
General	
UPS Topology	Line-interactive
Input	
Generator Compatibility	Yes
Nominal Input Voltage	230Vac ± 10%
Input Voltage Range	165 - 280Vac
Input Frequency Range	50/60 ± 5Hz (Auto-sensing)
Rated Input Current	2.72A
Plug Type	Schuko
Output	
VA/Watts	600/360
On Battery Waveform	Simulated Sine Wave
On Battery Voltage	230Vac ± 10%
On Battery Frequency	50/60Hz ± 1%
Automatic Voltage Regulation (AVR)	Single Boost, Single Buck
Overload Protection	Fuse
Outlets - Total	3
Outlet Type	Schuko x 3
Outlets - Battery & Surge Protected	3
Typical Transfer Time	4ms
Battery	
Runtime at 60W (min)	30
Runtime at 90W (min)	18
Battery Type	Sealed Lead-acid
User-replaceable	No
Typical Recharge Time	8 Hours
Surge Protection & Filtering	
Surge Suppression (Joules)	125
EMI/RFI Filtration	Yes
Management & Communications	
LED Indicators	Power On, Line Mode, Battery Mode, Low Battery
Audible Alarms	Battery Mode, Low Battery, Overload, UPS Fault
Physical	
Form Factor	Brick
Physical - UPS Module	
Dimensions (WxHxD) (mm.)	158 x 91.5 x 240
Weight (kg.)	3.8
Environmental	
Operating Temperature	32 °F to 104 °F / 0 °C to 40 °C
Operating Humidity	0% - 90% Non-condensing
Operating Elevation	0-10,000 feet (0-3,000 meters)
Storage Temperature	- 4 °F to 122 °F / -20 °C to 50 °C
Storage Relative Humidity	0% - 90% Non-condensing
Online Thermal Dissipation	40 BTU/hr
Certifications	
Certifications	CE
RoHS Compliant	Yes

#All specifications are subject to change without notice. ©2016 Cyber Power Systems, Inc. All Trademarks are the property of their owners.