



# RUT955 Router



Dual SIM



Linux powered

RoHS Compliant

ISO 9001



CERTIFIED ORGANISATION

## Description

RUT955 is highly reliable and secure LTE router for professional applications. Router delivers high performance, mission-critical cellular communication and GPS location capabilities. RUT955 is equipped with connectivity redundancy through dual SIM failover. External antenna connectors make it possible to attach desired antennas and to easily find the best signal location.



## Key Features

### Hardware

- LTE
- WiFi
- GPS
- 9 - 30 VDC
- 3 x LAN
- 1 x WAN
- 3 x Input
- 2 x Output
- RS232
- RS485
- microSD
- USB 2.0
- DIN Rail Mount
- Dual SIM

### Software

- OpenVPN
- PPTP
- Ping Reboot
- Web Filter
- IPsec
- Dynamic DNS
- GRE Tunnel
- L2TP
- Periodic Reboot
- SMS Control
- SNMP
- Mobile on Demand
- WiFi Hotspot
- VRRP
- Mobile Quota Control
- Backup WAN
- NTP
- Configuration Profiles
- RS232/485 Console
- RS232/485 over IP
- Input Triggers
- Samba Share
- Dual Image

If You think that this is not enough to win ALL Your potential customers - please contact us to get an advice on how to use it in Your application!

LTE

# Specifications



Technology/Version	Bands		
	EU/ASIA version	EU version	US version
LTE	FDD B1/B2/B3/B5/B7/B8/B20 (2100/1900/1800/850/2600/900/800 MHz)	FDD B3/B7/B20 (1800/2600/800 MHz)	FDD B2/B4/B5/B17 (1900/AWS-1/850/700b MHz)
3G	850/900/1900/2100 MHz	850/900/2100 MHz	850/1900 MHz
2G	850/800/1800/1900 MHz	900/1800 MHz	-

Technology/Version	Data rates (DL/UL)		
	EU/ASIA version	EU version	US version
LTE	100/50 Mbps	100/50 Mbps	100/50 Mbps
DC-HSPA+	43.2/5.76 Mbps	42/5.76 Mbps	43.2/5.76 Mbps
WCDMA	384/384 kbps	384/384 kbps	384/384 kbps
EDGE	236.8/236.8 kbps	296/236.8 kbps	-

## Ethernet

- IEEE 802.3, IEEE 802.3u standards
- 3 x LAN 10/100 Mbps Ethernet ports
- 1 x WAN 10/100 Mbps Ethernet port
- Supports auto MDI/MDIX

## WiFi

- IEEE 802.11b/g/n WiFi standards
- 2x2 MIMO
- AP and STA modes
- 64/128-bit WEP, WPA, WPA2, WPA&WPA2 encryption methods
- 2.401 – 2.495 GHz WiFi frequency range
- 20 dBm max WiFi TX power
- SSID stealth mode and access control based on MAC address

## Hardware

- High performance 560 MHz CPU with 128 Mbytes of DDR2 memory
- 2 pin industrial DC power socket
- Attachable DIN rail adapter
- 4 pin industrial socket for 2/4 wire RS485
- DB9 socket for full-featured RS232
- USB A socket for external devices
- Reset/restore to default button
- 2 x SMA for LTE, 1 x SMA for GPS, 2 x RP-SMA for WiFi antenna connectors
- 4 x Ethernet LEDs, 1 x power LED
- 1 x bi-color connection status LED, 5 x connection strength LEDs
- 10 pin industrial socket for inputs/outputs:
  - 0 - 3 V digital input
  - 0 - 30 V digital galvanically isolated input
  - 0 - 24 V analog input
  - 30 V, 250 mA digital open collector output
  - 40 V, 4 A SPST relay output



## Software

- OpenVPN, IPsec, GRE, L2TP, PPTP
- Backup WAN
- PPPoE
- Dynamic DNS
- SMS and ping reboot, periodic reboot
- Status, configuration via SMS
- Send/read SMS via HTTP POST/GET
- Monitoring by SNMP, SNMP trap
- System log to record the status of the router
- VRRP
- Web filter
- Wireless hotspot with or without RADIUS server
- SIM card switch controlled by signal, data limit, roaming
- RS232/485 serial console
- RS232/485 over IP
- Input triggers for SMS, e-mail, SIM card, profile, WiFi, reboot, output
- Configuration profiles
- Dual image with safemode firmware
- Firmware update from bootloader via WebUI
- Restore point



## Electrical, Mechanical & Environmental

- Dimensions (H x W x D) 80 mm x 106 mm x 46 mm
- Weight 280 g
- Power supply 100 – 240 VAC -> 9 VDC wall adapter
- Input voltage range 9 – 30 VDC
- Power consumption < 7 W
- Operating temperature -40 °C to 75 °C
- Storage temperature -45 °C to 80 °C
- Operating humidity 10 % to 90 % non-condensing
- Storage humidity 5 % to 95 % non-condensing

Teltonika reserves the right to modify the functionality of the device without any prior notice. Document version 1.10 (2015/09/08)  
 LTE is a trade mark of ETSI

HQ JSC Teltonika  
 Saltoniskiu str. 10C, LT-08105,  
 Vilnius, Lithuania  
 Phone: +370 5 2127472  
 Fax: +370 5 2761380  
 info@teltonika.lt  
 www.teltonika.lt