

S/FTP Cat. 6A LSZH patch cord, grey, 3 m

PP6A-LSZHCU-3M

- Perfect connection
- Dual shielded for a reliable connection
- Low Smoke Zero Halogen (LSZH) jacket
- Gold plated contacts



Features

- Patch cord with foil shielded pairs and braided cable, CAT 6A
- Gold plated contacts
- Low Smoke Zero Halogen (LSZH) jacket
- Molded strain reliefs
- Snagless boots

Packaging

| | |
|--------------------------------|----------------|
| Q'ty in crtn, pcs | 100 |
| Crtn volume, CUM | 0.038 |
| Crtn weight, kgs | 10.49 |
| Individual package size LxWxH: | 125x15x170 mm |
| Carton size LxWxH: | 400x290x330 mm |
| Country of origin | CN |
| Barcode | 8716309098601 |
| Customs code | 8544421000 |

Specifications

Patch cord category 6A SSTP (shielded)
Length: according to the item
Structure: AWG 27 (7 x 0.135 mm wire), COPPER
FM-PE insulation of the wire: 1.0 mm
With LDPE filler
With polyester tape
With aluminum foil
Drain hose: not used
With Braid : 16 x 4/0.12mm
Outer insulation: 5.8 mm
Color: according to the item
Operation up to 250 MHz

Certificates

